

SAFE Notice 2024

317

ALTERNATIVE BLOCKING ARRANGEMENTS AT MT VICTORIA INTERLOCKING

From Friday, 20 December 2024 until Saturday 21 June 2025, the following Safeworking arrangements will apply:

THIS SAFE NOTICE CANCELS AND REPLACES SAFE NOTICE 220 – 2024 DUE TO EXPIRY.

In conjunction with Operational Instruction OI N 23-01 the following alternative arrangements will apply in the Mt Victoria interlocking until further notice.

Block working of rail traffic

If it is necessary to block work rail traffic on the Up Main line beyond the Mt Victoria interlocking, in addition to the application of blocking at Mt Victoria, the block working section must be established and maintained between Newnes Junction and Katoomba. The Signaller must apply and maintain blocking facilities to signals at the entry to the block working section at Newnes Junction until rail traffic has arrived clear at Katoomba.

If it is necessary to block work rail traffic on the Down Main line beyond the Mt Victoria interlocking, in addition to the application of blocking at Mt Victoria, the block working section must be established and maintained between Katoomba and Newnes Junction and the Signaller must apply and maintain blocking facilities to signals at the entry to the block working section at Katoomba until rail traffic has arrived clear at Newnes Junction.

Work on track authorities and methods using Controlled Absolute Signals, or Activities associated with in-service rail traffic.

If it is necessary to implement a Work on track authority or method, or to protect activities associated with in-service rail traffic on the Up Main line for a worksite between MV 78 and the yard limits at Katoomba, in addition to placing protecting signals at STOP with blocking facilities applied, the Signaller must:

- arrange for signals NJ 8 and NJ 10 at Newnes Junction to be placed at STOP with blocking facilities applied, and
- arrange for the Protection Officer to clip and lock points in the Mt Victoria interlocking to prevent entry to the authority limits, worksite, or activity location.

SAFE Notice No. 317 - 2024 Page 1

Temporary SAFE Notice

If it is necessary to implement a Work on track authority or method, or to protect activities associated with in-service rail traffic on the Down Main line for a worksite between MV 1 and the Yard limits at Newnes Junction, in addition to placing protecting signals at STOP with blocking facilities applied, the Signaller must:

- arrange for signals KT 17 and KT 19 at Katoomba to be placed at STOP with blocking facilities applied, and
- arrange for the Protection Officer to clip and lock points in the Mt Victoria interlocking to prevent entry to the authority limits, worksite, or activity location.

If protection is to be implemented for work within Mt Victoria yard, in addition to Controlled Absolute Signals being placed at stop with blocking facilities applied, the Signaller must arrange for the Protection Officer to clip and lock points to prevent entry to worksite, or activity location.

Work Protecting Conditions Affecting the Network or restraining rail traffic.

If it necessary to use controlled absolute signal at STOP at Mt Victoria to protect a Condition Affecting the Network, or to restrain rail traffic at a Controlled Absolute Signal, in addition to the protecting signals being placed at STOP with blocking facilities applied, a written CAN form must be issued to the Driver or Track Vehicle Operator in accordance with *NGE 206 Condition affecting the network*.

SYDNEY, 05 DECEMBER 2024 DIRECTOR NETWORK STANDARDS, SYSTEMS & QUALITY SYDNEY TRAINS

Returned to Controlling Manager:	Date:	Signed:
2		
(Cut along this line and forward the detached receipt to your Controlling Manager)		
To Controlling Manager:	Date:	Signed:
Received SAFE Notice No. 317 – 2024	Date:	Signed:
Name (print):		

SAFE Notice No. 317 - 2024 Page 2

FOR THE INFORMATION OF EMPLOYEES AND NOT FOR PUBLICATION