

MGE 202 Handsignals

Purpose

To prescribe the rules for giving and responding to handsignals used in the Network.

Principle

Giving handsignals

Handsignals must be given:

- in a clear and timely manner, and
- so that they will be received and acted upon only by those who are being signalled.

A Handsignaller must:

- be in or have access to a safe place, and
- be in clear view of those who are being signalled, and
- as required, have effective communication with Signallers or Protection Officers.

Responding to handsignals

If the meaning of a handsignal is not understood, Drivers and Track Vehicle Operators must stop to find out the meaning.

Drivers and Track Vehicle Operators must:

- obey handsignals, and
- acknowledge handsignals other than shunting handsignals.



general NGE 202 Handsignals

Handsignalling

Handsignals must be given using:

- flags or hands during daylight, and
- lights during darkness and low visibility.

A handsignal must be continued:

- for the PROCEED and PROCEED AT CAUTION handsignal, until the cab of the leading rail vehicle has passed the Handsignaller, and
- for STOP handsignals, until the rail traffic has stopped.

If at a signal, a Handsignaller must:

- be able to see whether the signal is at STOP, and
- if rail traffic is required to stop, give a STOP handsignal until rail traffic has stopped.

If the signal being held at STOP clears, the Handsignaller must:

- tell the Signaller to set the signal at STOP, and
- tell the Protection Officer, if provided.

A Handsignaller must stand well away from signals if:

- rail traffic is not required to stop, or
- not signalling at a signal.

STOP handsignals

Drivers and Track Vehicle Operators must stop their trains or track vehicles if they, or other crew members, receive a STOP handsignal given by:

- a red flag, or
- a red light, or
- both hands held high.



general

NGE 202 Handsignals

ALL CLEAR handsignals

Drivers or Track Vehicle Operators must sound the whistle to acknowledge an ALL CLEAR handsignal given by:

- a white light, or
- one hand held high.


DANGER handsignals

Drivers or Track Vehicle Operators must stop their trains or track vehicles immediately if they, or other crew members, receive a DANGER handsignal given by vigorous waving of:

- arms, or
- a flag, or
- a light.

General handsignals

The following diagrams show the handsignals that must be used in the Network. STOP






general

NGE 202 Handsignals

PROCEED AT CAUTION





Note

When a PROCEED AT CAUTION handsignal:

- is given by an inner Handsignaller protecting a worksite, Drivers or Track Vehicle Operators
 must, unless otherwise advised by that Handsignaller, not exceed a maximum speed of
 25km/h until the rail traffic has passed the worksite limits, or
- is given by other Qualified Workers, Drivers or Track Vehicle Operators must proceed at restricted speed.

PROCEED






general

NGE 202 Handsignals


ALL CLEAR - I AM AWARE OF YOUR APPROACH



Shunting handsignals

Shunting handsignals must be given as necessary until the end of the planned movement.

MOVE AWAY






general NGE 202 Handsignals

MOVE AWAY AT CAUTION




Swing green light backwards and forwards beside the body



Move one hand and forearm in circular motion, with other hand raised high


MOVE TOWARDS ME





general NGE 202 Handsignals

MOVE TOWARDS ME AT CAUTION



Wave green light slowly



Wave one arm slowly over head, with other hand raised high

Related Documents

Nil

