

Precautions during signalling equipment testing

Purpose

To prescribe the precautions required during testing of signalling equipment in the Network.

General

Changing signal indications

Testing of signalling equipment must not be conducted if:

- rail traffic is closely approaching a signal, and
- the testing could change the signal indication.

If rail traffic is standing at a signal at **STOP**, the Signaller must:

- before testing the signal, tell the Driver or Track Vehicle Operator that their train or track vehicle must not move unless instructed to do so, and
- after testing the signal, tell the Driver or Track Vehicle Operator that the testing has been completed and, if required, give an authority to proceed.

Precautions during signalling equipment testing

Inspection, maintenance and testing of points protecting a work on track authority

Points that are clipped and locked to protect a work on track authority may be unclipped for inspection, maintenance or testing only if:

- agreed to by the:
 - Possession Protection Officer for a Local Possession Authority (LPA), or
 - Protection Officer for a Track Occupancy Authority or Track Work Authority.
- Absolute Signal Blocking or a work on track authority is in place to prevent rail traffic from approaching the points while they are unclipped.

The Possession Protection Officer or Protection Officer must make sure that rail traffic within the work on track authority is prevented from approaching the points while they are unclipped.

Recording test results

Signallers and Qualified Workers must record signalling equipment test results in permanent form.

signals and signs

Precautions during signalling equipment testing

Network Procedures

- NPR 721 Spoken and written communication*
 - NPR737 Switching a signal box or local control panel in and out*
 - NPR 747 Using Drivers time-release buttons*
-

Effective date

04 December 2022

pre-release