

ATWS Worksite Protection for Mt Kuring-Gai Condition Monitoring Equipment Maintenance

WORK DESCRIPTION	Routine Maintenance activities
WPP Number	CMO9BWS 10001
SCOPE:	Routine maintenance activities performed by Condition Monitoring Operations team. - on the Up and Down Main North lines between 39.601 km to 39.716 km - that does not involve the use of tools or equipment, or - using tools which can be easily and immediately removed from the track by one person and are light, non-powered hand tools, or light battery powered tools or devices.
AUTHORISATIONS:	Protection Officer, ATWS Operator (Operator) & ATWS Installer (Installer): - Protection Officer (PO) Level 1 – 4, and - WATWS – Wireless Automatic Track Warning System
PERSONAL PROTECTIVE EQUIPMENT	High visibility vest, boots, high visibility lookout sleeve
SAFETY CONTROLS – Lookout Working (ATWS) arrangements:	- Automatic Track Warning System (ATWS) - provides visual and audible warning for workers - ATWS sensor for Up direction running on the Up Main line at 40.426 km - ATWS sensor for Down direction running on the Down Main line at 39.029 km IMPORTANT! - This document must not be used to install or adjust the ATWS sensors - All sensors in the plan and shown on the diagram must be connected to transmit a warning
PRESTART REQUIREMENTS:	Refer to D2015-45354 Wireless ATWS (Automatic Track Warning System) to install or remove sensors
FURTHER INFORMATION:	Refer to “D2015-45354 Wireless ATWS (Automatic Track Warning System)” for detailed instructions to set-up, connect, test and operate the ATWS system with pre-installed ATWS sensors

Required ATWS Equipment		
Item	Description	Quantity
Aerial	Telescopic Aerial	3
Assembly Kit	Orange Bag with Tools	1
Battery ZA24-2.9	Small battery for Junction Box & Transmitter	4
Device Frame	Protective Frame	3
F500-AB Junction Box	Receiver Device	2
F500-SEN Train Sensor	Sensor	2
Housing for Aerial	Housing for Telescopic Aerial	3
KF5-5 Extension Cable	Extension Cable (5m) for F500-SEN to F500-AB	0
Mobile Backpack	Harness for Device	0
Pouch	Pouch for small battery	2
Tripod	Tripod for Device	3
ZFS Radio Transmitter	Radio Transmitter Device	2
ZPW Warning Unit	Control & Warning Device	1

Protection Officer/Operator assessment checklist

Protection Officer's name:		Yes (Tick if Yes)
This document has not expired 12 months beyond the issue date.		
SWI details and protection arrangements have been reviewed and validated for the assessed worksite location, including: - On-site safety assessment has been completed for relevancy of works being undertaken - The required protection details, environment and tasks are unchanged from the details of this SWI - All boxes have been ticked if applicable and crossed if not applicable - All fields have been completed		
Corridor Safety Number	Protection Officer Signature	Date

**Warning:**

If an above item does not apply, the Protection Officer must not use this Safe Work Instruction. A new worksite protection plan must be completed in accordance with NRF 014 Worksite Protection Pre-work briefing and NRF 015 Worksite Protection Plan.

Worksite Protection Pre-work BriefingBriefing date: **Protection Officer details**

name	signature	contact no.
------	-----------	-------------

Work location:

Scope of work:

Worksite protection:

Lookout Working (ATWS)

 Refer to Worksite Protection Plan for details

Hazards (e.g. environment, plant, equipment, human error)	Controls (to be implemented to eliminate or reduce the risk to the lowest practicable level)	Person responsible for Control
Crossing live lines	A qualified Protection Officer (PO) or Access Corridor Safety (ACS) must make a safety assessment to cross live lines in accordance with NGE200 and supervise workers who do not hold the PO or ACS qualification.	Qualified PO/ACS
Accessing Danger Zone to conduct plate test	Use appropriate safety measures as validated by a PO. Refer to diagram for minimum safety assessment.	Qualified PO
Electricity	ATWS antennae not to encroach safe approach distance to overhead wiring	Operator
Slips, trips, falls carrying ATWS equipment	Use correct manual handling techniques, secure safety boots, clear obstacles for work area and agree a safe path.	All
Approaching rail traffic	- Lookout Working using approved ATWS as assessed in the plan & diagram. - All points of entry have been validated and ATWS safety measures (sensors) have been installed. - Confirm with the Operator that the ATWS has been tested and is operational. - Workers immediately move to the designated safe place when warned. - Provide ALL CLEAR handsignal after workers and equipment are in a safe place. - After the warning has been cancelled, confirm there is no approaching rail traffic between the sensors and the worksite before allowing work to resume.	PO
Ineffective ATWS warnings / Adjoining / surrounding worksites	- Test and confirm workers can see and hear the warning in the noisiest environment. - Explain the emergency warnings. - Workers to be within 50m of warning device. - Workers to remain within sight and hearing of warning unit at all times. - Radios not to be used near ATWS.	PO
Train warning time longer than expected (stopping points or ATWS equipment fault)	Workers to remain in a safe place until confirmed the ATWS is working correctly. Contact the Signaller or visually confirm the line is clear between the sensors and the worksite. Potential stopping points: Down Main – N 24.51 Signal	PO
Adjacent live lines	Remain within the tracks being protected by the ATWS	PO
Second train warning cancelled in error	- Nominate a team member to confirm with the Operator when each rail traffic has completely passed the worksite. - Tell the PO and workers about the second train warning. - Cancel each warning after each train has completely passed the worksite.	Operator / nominated team member
Distraction	Obtain permission from PO to use electronic devices in the Danger Zone.	All
Obstructions to safe place	Agree on paths to reach designated safe places from the worksite.	PO
Electrical storms	Stop work immediately	All

☐ A final site inspection has been conducted immediately before commencing work, and any new hazards and controls have been included.

name _____ signature _____ contact no. _____

Participant acknowledgement

NOTE: Recipients of the briefing are to question the Briefer if they don't understand any part of this briefing.

All workers listed below acknowledge that they:

1. hold the applicable and current Rail Safety Worker Authorisation
2. have been briefed on the identified hazards and controls
3. have been briefed on the risks from adjacent lines and/or worksites
4. have been briefed on the planned worksite protection
5. understand the limits of the worksite
6. have been briefed on the contents of the Worksite Protection Plan
7. have been shown the worksite protection diagram or map

[illegible]

Worksite Protection Plan – Lookout Working

Signaller details

	Hornsby Main Panel	02 9701 1510
	Hornsby North Panel	02 9701 1513

Protection Officer details

name	signature	contact no.
RSW or RIW No.	designation	Planned duration

Workplace Supervisor details:

 Type of work: **Routine Maintenance Activities**

Worksite location

On the	Up Main North line		☐
between	N 25.20 Auto Signal	and	N 24.66 Auto Signal
On the	Down Main North line		☐
between	N 24.51 Auto Signal	and	N 25.21 Auto Signal

Worksite Assessment

 The Lookout Working Prohibited Locations Register been consulted Yes ☐

Warning method

ATWS

Minimum Warning Time Calculations

 Maximum track speed **105 km/h**

Number of ATWS Sensors used			1 / 2	Position of ATWS Sensors		39.029 km	and	40.426 km														
<table><tr><td>7 sec</td></tr><tr><td>7 sec</td></tr></table>	7 sec	7 sec	+	<table><tr><td>3 sec</td></tr><tr><td>3 sec</td></tr></table>	3 sec	3 sec	+	<table><tr><td>10 sec</td></tr><tr><td>10 sec</td></tr></table>	10 sec	10 sec	= Minimum Warning Time (MWT)	<table><tr><td>20 sec</td></tr><tr><td>20 sec</td></tr></table>	20 sec	20 sec	<table><tr><td>105 km/h</td></tr><tr><td>100 km/h</td></tr></table>	105 km/h	100 km/h	<table><tr><td>584 metres</td><td>Down Main line</td></tr><tr><td>556 metres</td><td>Up Main line</td></tr></table>	584 metres	Down Main line	556 metres	Up Main line
7 sec																						
7 sec																						
3 sec																						
3 sec																						
10 sec																						
10 sec																						
20 sec																						
20 sec																						
105 km/h																						
100 km/h																						
584 metres	Down Main line																					
556 metres	Up Main line																					
See Time (S)		Move Time (M)		Safe Time	(S+M+10 sec = MWT)		Track speed	Minimum Sighting Distance as calculated														

Where are the safe places identified for the ATWS Operator, Lookouts and workers?

Lookouts:	N/A
Workers:	Up Cess for Up Main. Down Cess for Down Main.

 Confirm mandatory first train tests were completed for all sensors Yes ☐

 Ensure the workers have been briefed about these work details Yes ☐

NOTE: Diagrams and instructions that follow form part of this worksite protection plan.

ATWS Check-sheet

Planning

1. How will the installed location of sensor(s) be verified?

- ☐ The PO will have direct line of sight to the sensor from the worksite location
- ☐ The installer will travel from the sensor location to the worksite location on the same side of track
- ☐ The ID no. of the first train will be verified between the operator and installer

Train ID # observed:

Verified by installer: ☐ (tick to confirm)

Testing

2. Record evidence of mandatory First Trains Tests:

- a. Record Train ID # or type of train observed for all sensors:

- b. Confirm mandatory first train tests are complete for all sensors installed
- ☐
- (tick to confirm)

Pre-work Briefing


3. Identify potential stopping points affecting warning times:

Record any potential stopping points e.g. (stations or signals) between the sensor(s) and worksite which could cause variable warning times:


Note: Factors affecting warning times should be highlighted to staff during the pre-work brief

Tick if used ☐

Worksite on Up & Down lines




UNCONTROLLED COPY WHEN PRINTED



UNCONTROLLED COPY WHEN PRINTED

Tick if used ☐

Worksite on Down Main line



UNCONTROLLED COPY WHEN PRINTED

INSTRUCTIONS:	Workers enter the rail corridor via access gate N00 39.613 D. Use assets to validate worksite location on Up and Down Main lines between 39.601 km to 39.716 km Conduct WP Pre-work briefing to set-up ATWS. Tell Signaller at Hornsby Main and/or Hornsby North Panel about the use of lookout working with ATWS.
Tick if used ☐	Access Up Cess 40.426 km, verify sensor label & connect to sensor cable, calibrate with test plate, connect and turn on the transmitter. ZFS Radio ID: AU: Time:
Tick if used ☐	Access Dn Cess 39.029 km, verify sensor label, connect to sensor cable, calibrate with test plate, connect & turn on transmitter. ZFS Radio ID: AU: Time:
	Place warning system on same side of tracks if working on one track only within sight & hearing of workers, conduct siren & light self-test, & connect to transmitter(s). ZPW ID: AU: Time: Record first rail traffic movement test for each sensor on ATWS Check-sheet. Conduct WP Pre-work briefing for lookout working with ATWS and confirm workers have seen and heard the warning. Start work when advised by the PO and move to the designated safe place when warned. When work is complete, and workers and equipment are in a safe place, turn off and pack up warning unit
Tick if used ☐	Access Up Cess to turn off and pack up transmitter unit(s).
Tick if used ☐	Access Dn Cess to turn off and pack up transmitter unit(s).
	Access Down Cess for all workers to leave the rail corridor via access gate N00 39.613 D. Tell Signaller at Hornsby Main and/or Hornsby North Panel when work is completed and the workers and their equipment are clear of the Danger Zone.

Tick if used ☐ Position of ATWS transmitter and sensor on **Down Main North** line at **39.029 KM**



Image 1: Sensor and transmitter installation location



Image 2: Sensor access using access gate **N00 38.953 D**

Tick if used ☐ Position of ATWS transmitter and sensor on **Up Main North** line at **40.426 KM**



Image 1: Sensor and transmitter installation location



Image 2: Sensor access using access gate **N00 40.424 D**

[illegible]