

General NGE 220 Unreliable track-circuit operation

Description

This document describes the requirements for identifying and responding to unreliable track-circuit operation.

Not what you are looking for? See more NGE Rules

Purpose

To prescribe the rules for identifying and responding to unreliable track-circuit operation in the Network.

Identifying unreliable track-circuits

Reporting

Qualified Workers must report track-circuits suspected of being faulty to the Signaller.

The Signaller must treat the operation of the reported track-circuits as unreliable.

Intervals between train movements

Signallers must treat the operation of track-circuits that have not been travelled over by rail traffic for 72-hours or more as unreliable.



The responsible Signal Engineer may specify a period longer or shorter than 72-hours for designated portions of track.

Responding to unreliable track-circuits

Rail traffic detection failure



General NGE 220 Unreliable track-circuit operation

Track-circuit operation must be treated as failed and in an unsafe condition if it fails to provide an indication when a train, or a track vehicle listed in the <u>Train Operating Conditions (TOC) manual</u> as operating track-circuits, is on the track-circuit.

Signallers who become aware that track-circuit detection of rail traffic might have failed must:

- set controlled signals allowing entry to the affected blocks at **STOP** and apply blocking facilities, and
- arrange for the Signals Maintenance Representative to be told about the unreliable trackcircuits, and
- make sure that signalling equipment affected by unreliable track-circuits is not used before it is tested and certified as working correctly by the Signals Maintenance Representative, and
- tell the Network Controller, and
- block work rail traffic.

False detection of rail traffic

Track-circuit detection is treated as false if it indicates that the track-circuit is occupied without rail traffic being present.

Signallers who become aware that track-circuits are providing a false indication of the presence of rail traffic must arrange for the Signals Maintenance Representative to certify the track-circuits as working correctly.

Until the track-circuits have been certified as working correctly, rail traffic must be worked in accordance with:

- NSY 512 Manual block working, or
- NSG 608 Passing signals at STOP.



General NGE 220 Unreliable track-circuit operation

Related Documents

NPR 722 Manual block working

NPR 746 Authorising rail traffic to pass an absolute signal at STOP