

## Description

This document describes the requirements for using Automatic Train Protection (ATP) onboard equipment.

Not what you are looking for? See more NTR Rules

### Purpose

To prescribe the rules for using Automatic Train Protection (ATP) onboard equipment.

## Principle

This Network Rule applies only to:

- trains approved to operate in the Network with operating ATP equipment
- Drivers qualified to operate the ATP equipment.

ATP onboard equipment fitted to the leading cab of a train must be operating in accordance with the *Train Operating Conditions (TOC) manual* before the train may enter the Sydney Trains Network.

Drivers must report faults in ATP onboard equipment to the Signaller.

## Warning

The maximum speeds allowed by ATP do not imply that it is safe to travel at those speeds.

### **Isolating ATP equipment**

The ATP equipment in an active Drivers cab may be isolated only if a fault cannot be remedied by the Train Crew, and the fault prevents travel.

If the ATP equipment in an active Drivers cab is isolated, the Driver must tell the Signaller.



### ATP levels

#### Automatic level transitions

ATP level transitions are announced by a balise group before each level boundary.

On running lines, level transitions should automatically occur at the boundary between the areas with different ATP levels.

#### Missed level transitions

If a level transition does not occur at a signposted location, the Driver must:

- treat the inconsistency as a Condition Affecting the Network (CAN)
- stop and manually change the ATP level in the active cab.

## Note

If a train crosses a level transition border in Shunting mode, the level transition will not occur until Shunting mode is exited.

### Manually selecting an ATP level

When required by the system, Drivers must select the correct ATP level for their current location.

### Activating modes

#### Shunting (SH) mode

Shunting (SH) mode must be activated by the Driver:

- to make authorised propelling movements, or
- to divide a train or amalgamate trains, or
- to shunt within shunting yards and sidings.



Shunting (SH) mode must be exited before a non-propelling through movement is commenced.

#### Non leading (NL) mode

Non-Leading (NL) mode may be activated in a cab only with the authority of the Network Controller.

Non-Leading (NL) mode must be exited after the movements for which it has been authorised have been completed.

#### Wrong running-direction movements

For wrong running-direction movements on unidirectional lines in ATP level 1 areas, the ATP system will enforce:

- a 40km/h maximum speed
- 15km/h maximum speed on the approach to active control level crossings.

### Using the override function

Drivers may activate the ATP override function only if they receive an ATP message requiring them to do so.

### Setting train data

Drivers must accurately confirm or enter the ATP level, the train length and airbrake cutout information into the onboard system:

- when required by the system
- if the data change.

#### Interventions

Drivers must tell the Signaller if there is an ATP emergency brake intervention.



## Trackside faults

Drivers must treat a suspected fault in trackside ATP equipment as a Condition Affecting the Network (CAN).



ATP onboard equipment can display messages that relate to trackside faults.

If a CAN about trackside ATP equipment is reported, the Signaller must tell the Driver of the next ATP-fitted train to report if an error message is received at the affected location.

If the Driver of the following ATP-fitted train also reports the equipment as faulty, the Signaller must:

- arrange for a Signals Maintenance Representative to attend
- give a CAN warning to Drivers of ATP-fitted trains.

### Precautions for people under trains

Train Crews must disconnect power to a vehicle's ATP antenna:

- before any person goes beneath the vehicle, or
- if anyone is struck by the train.

The ATP antennas must not be re-powered until people are no longer beneath the vehicle.

## Warning

ATP antennas generate electromagnetic radiation that can be harmful to people underneath them.

### ATP messages



Messages shown on the Driver machine interface (DMI) must be read and understood by Drivers before they act upon them.

If a message begins with 'Report Balise fault', Drivers must tell the Signaller.