

NSG 606 Responding to signals and signs

Description

This document describes the requirements for responding to signal indications and signs.

Not what you are looking for? See more [NSG Rules](#)

Purpose

To prescribe the rules for responding to signal indications and signs in the Network.

Principle

Fixed signals are devices near lines to:

- separate and regulate rail traffic
- tell Drivers, Track Vehicle Operators and other Qualified Workers about the status of the line ahead
- show which route is set.

There might be permanent or temporary signs instead of fixed signals.

Drivers, Track Vehicle Operators and Qualified Workers directing shunting and propelling movements must obey the indications and instructions displayed by signals, indicators and signs.

Changing signal indications

If rail traffic is closely approaching a signal, the Signaller must not change the indication of the signal to a more restrictive aspect unless there is a Condition Affecting the Network (CAN).

If rail traffic is standing at a signal, the Signaller must not change the indication of the signal to a more restrictive aspect unless:

- there is a CAN, or
- the route needs to be altered, and it is safe to do so.

If possible, the Signaller must arrange for the Driver or Track Vehicle Operator to be told about the change of the signal aspect.

NSG 606 Responding to signals and signs

Signals must be tested in accordance with NSG 616 Precautions during signalling equipment testing.

Route and locality knowledge

Qualified Workers who observe, operate or maintain fixed signals must know the locations and purposes of signals in their areas of work.

Limit of authority

The clearing of a signal gives authority to enter the block for which the signal has been cleared.

Running signals

A running signal authorises a through-movement between that signal and the next running signal.

Other than for shunting movements, Signallers must not clear a running signal if the block ahead is occupied.

A Signaller may use a running signal to authorise a shunting movement if:

- there is no shunting signal available
- the Driver or Track Vehicle Operator has been told.

Shunting signals

A shunting signal authorises a movement at restricted speed past that signal.

If possible, Signallers must use shunting signals to authorise shunting movements.



Warning

Shunting signals can be cleared if the line beyond the signal is occupied. Drivers and Track Vehicle Operators must proceed as if the line is already occupied.

NSG 606 Responding to signals and signs

Unless the Signaller instructs that a movement is to proceed for a shorter distance, a **PROCEED** indication by a shunting signal is an authority to proceed up to and not beyond the first of the following limits reached:

- **SHUNT LIMIT** sign
- **STOP** sign
- indicator showing that points are not set, catch points are open, or a derail device is set on the rail
- set of non-interlocked points
- signal for the direction of travel.

A Signaller may use a subsidiary shunting signal to authorise rail traffic to pass a home signal, if the running signal:

- fails to clear, or
- cannot be cleared because rail traffic occupies the line beyond the signal.

A Signaller must not use a subsidiary shunting signal as the sole authority for rail traffic to pass a starting or home/starting signal for a through movement. The movement must be made in accordance with NSG 608 Passing signals at STOP.

If a subsidiary shunting signal is used to authorise rail traffic to pass a running signal at **STOP**, the Driver or Track Vehicle Operator must proceed at restricted speed.

Signal indications

STOP

Rail traffic must stop before a signal at **STOP**.

Drivers or Track Vehicle Operators must keep the signal indication clearly in view.

If both a co-acting signal and the associated primary signal display **STOP**, rail traffic may pass the co-acting signal but must stop at the associated primary signal.

Signals may be passed at **STOP** only in accordance with NSG 608 Passing signals at STOP.

NSG 606 Responding to signals and signs

PROCEED

A **PROCEED** indication shows that:

- interlocked points protected by the signal are set in the correct position for the movement
- no conflicting route has been set.

Other than for shunting movements, a **PROCEED** indication by a running signal shows that the block is unoccupied as far as the next running signal.

A **PROCEED** indication by a shunting signal does not indicate that the block ahead is unoccupied.

LOW SPEED

Low speed signals are small in-line green lights:

- in or below the bottom of the lower case of double colour light signals, or
- below the main lamp case of single colour light signals.

Low speed aspects indicate that the line to the next signal is unoccupied. They authorise rail traffic to proceed, but to expect:

- the next signal to be at **STOP**
- the line beyond the next signal to be occupied.

If train stops are provided, the maximum permitted speed is 25km/h. Intermediate train stops may require further speed reduction.

CLOSE UP

CLOSE UP signals indicate that the line to the next signal is unoccupied. They authorise rail traffic to proceed, but to expect the next signal to be at **STOP**.

Note

The line may be occupied immediately beyond the next signal.

NSG 606 Responding to signals and signs

Irregular signal indications

A fixed signal indication must be treated as **STOP** if:

- it is an illegal signal indication, or
- there is no indication, or
- there is no indication other than the route indicator, or
- it is not understood.

Illegal signal indications

A signal indication is illegal if it is not consistent with:

- the aspects and indications used in the Network
- the indications of adjoining signals and the known condition of the line
- what is known about occupancy of the line.

Qualified Workers must report illegal signal indications to the Signaller responsible for the portion of track.

The Signaller must:

- if the affected signal is a controlled signal, set the affected signal to **STOP** with blocking facilities applied
- give Drivers and Track Vehicle Operators a CAN warning about affected automatic signals
- tell the Network Controller
- tell a Signals Maintenance Representative.

Affected signals must not be used to provide **PROCEED** indications before they have been certified back into use.

Partial indications

Colour light running signals

NSG 606 Responding to signals and signs

If a light in a colour light running signal is not visible, Drivers or Track Vehicle Operators must act as if the aspect is the most restrictive combination for the remaining displayed lights.

Colour light signals with route indicators

If a colour light signal shows a **PROCEED** indication without the route indicator being visible, Drivers or Track Vehicle Operators must obey the **PROCEED** indication.

Semaphore signals

If, in darkness, no lights are displayed by a semaphore signal, Drivers or Track Vehicle Operators must obey the indication displayed by the signal arm.

Signals not in use

A signal that is not in use must:

- have a large white “X” hung over the signal, or
- if next to a functioning signal, have its head covered or turned away from the line.

Drivers or Track Vehicle Operators must ignore indications of signals marked as not in use.

Signal placement

Signals for a unidirectional line are preferably to the left of the line in the direction of travel. If this is not possible, they may be placed:

- above the line, or
- to the right of the line.

Signals for a double line bidirectional line are usually:

- for travel in the usual running direction, to the left of the line
- for travel opposite to the usual running direction, to the right of the line.

If a signal is placed to the right of the line, a left pointing arrow may be used to indicate the line to which the signal applies.

NSG 606 Responding to signals and signs

Running signal indications

The legal **PROCEED** and **STOP** indications shown by colour light and semaphore signals in the Network are, from least restrictive (highest) aspect to most restrictive (lowest) aspect:

Note

In the figures, lunar white lights are shown in blue ; pulsating lights are shown with radial lines .

Single colour light

CLEAR

PROCEED. Next signal displays a **PROCEED** indication.




Signals and Signs

NSG 606 Responding to signals and signs

**MEDIUM**

PROCEED. Next signal displays at least a **CAUTION** or **CAUTION TURNOUT** indication.


**MEDIUM TURNOUT**

PROCEED on turnout route. Next signal displays at least a **CAUTION** or **CAUTION TURNOUT** indication.

**CAUTION**

PROCEED. Next signal may be at **STOP**.

NSG 606 Responding to signals and signs



CAUTION TURNOUT

PROCEED on turnout route. Next signal may be at **STOP**.




LOW SPEED

PROCEED ready to stop at the next signal.

NOTE: The line immediately beyond the next signal may be occupied.

Where train stops are provided, a maximum speed of 25km/h applies.




CLOSE UP

PROCEED ready to stop at the next signal.


NOTE: The line immediately beyond the next signal may be occupied.

Signals and Signs


NSG 606 Responding to signals and signs



Double colour light



NSG 606 Responding to signals and signs



PRELIMINARY MEDIUM

PROCEED. Next signal displays at least a **MEDIUM** indication.



MEDIUM

PROCEED. Next signal displays at least a **CAUTION** or **CAUTION TURNOUT** indication.



MEDIUM TURNOUT

PROCEED on turnout route. Next signal displays at least a **CAUTION** or **CAUTION TURNOUT** indication.

NSG 606 Responding to signals and signs

**CAUTION**

PROCEED. Next signal may be at **STOP**.

**CAUTION TURNOUT**

PROCEED on turnout route. Next signal may be at **STOP**.

**LOW SPEED**

PROCEED ready to stop at the next signal.

NOTE: The line immediately beyond the next signal may be occupied.

Where train stops are provided, a maximum speed of 25km/h applies.

NSG 606 Responding to signals and signs



CLOSE UP

PROCEED ready to stop at the next signal.


NOTE: The line immediately beyond the next signal may be occupied.



STOP


Single lower quadrant

NSG 606 Responding to signals and signs



CLEAR

PROCEED. Next signal may be at **STOP** or **CLEAR**.



STOP

Repeater signals

Colour light repeater signals take the same form as colour light running or shunting signals.


The repeater signal might show a less restrictive indication than the repeated signal.

Indications displayed by other repeater signals used in the Network are:


Repeater signal - LEDs

Signals and Signs

NSG 606 Responding to signals and signs




PROCEED. Next signal shows PROCEED.




PROCEED. Next signal shows STOP.

Repeater signal - position lights

NSG 606 Responding to signals and signs



PROCEED. Next signal shows PROCEED.



PROCEED. Next signal shows STOP.

LANDMARK and LOCATION signs

LANDMARK and LOCATION signs warn Drivers and Track Vehicle Operators that they:

- are approaching a location
- must be ready to respond to the first signal, **STOP** sign, or **YARD LIMIT** sign at the location.

LANDMARK sign

NSG 606 Responding to signals and signs



PROCEED being prepared to respond to the first signal, **STOP** sign, or **YARD LIMIT** sign.

LOCATIONS sign



PROCEED being prepared to respond to the first signal, **STOP** sign, or **YARD LIMIT** sign.

YARD LIMIT signs

If the Driver or Track Vehicle Operator does not have authority for the movement, rail traffic must not pass a yard limit sign.

Common form of arrival end **YARD LIMIT** sign.

NSG 606 Responding to signals and signs

Act in accordance with the Proceed Authority.



Common form of departure end **YARD LIMIT** sign.

Act in accordance with the Proceed Authority.



Related Documents

NPR 721 Spoken and written communication

NPR 746 Authorising rail traffic to pass an absolute signal at STOP

Signals and Signs

NSG 606 Responding to signals and signs