

## Form Procedures

# NPR 011 Using a Worksite Warning Form

## Description

This document describes how a Worksite Warning form must be compiled, issued, cancelled, fulfilled and managed.

Not what you are looking for? See more [Form Procedures](#)

## Introduction

*NRF 011 Worksite Warning* is used to advise Drivers and Track Vehicle Operators about the locations of worksites and speed restrictions.

This form is used:

- if multiple worksites are established under a Track Work Authority (TWA), or
- during pilot staff working, if rail traffic has to pass more than six worksites, either on the line used for pilot staff working or on the adjacent line.

If rail traffic has to pass more than six worksites during pilot staff working, the Qualified Worker must make sure that on the *NRF 008 Pilot Staff Notice (PSN)*:

- item 7 is ticked  **7** , and
- the check box  beside the statement 'There are more than six worksites' is ticked.

The Qualified Worker who prepares the Worksite Warning form must arrange for it to be given to the Driver or Track Vehicle Operator:

- if pilot staff working is in operation, before the rail traffic enters the pilot staff section, or
- if a TWA has been issued, by the inner Handsignaller before rail traffic enters the portion of track covered by the TWA.

## Mandatory items

The following items must be completed:

1 Worksites are located

3 Worksite locations and speeds

5 Issued to

Form Procedures

# NPR 011 Using a Worksite Warning Form

6 Issued by

## Optional items

The following items are optional:

2 Handsignallers

4 CLEARANCE sign

Review each item, and:

- put a cross in the numbered box  if the item does not apply in this instance, or
- tick the numbered box  if the item applies in this instance and complete the details.

### Item 2 – Handsignallers

If there are Handsignallers tick the numbered box  and complete the details.

### Item 4 – CLEARANCE sign

If there is a CLEARANCE sign at the end of the work tick the numbered box  and complete the detail.

## Form Procedures

# NPR 011 Using a Worksite Warning Form

FIGURE 1: NRF 011 Worksite Warning

RailSafe

Worksite Warning – NRF 011

  

**1** Worksites are located between  km and  km

**2** Handsignalers are located at  Sig/km

Sig/km

Sig/km

Sig/km

Sig/km

Sig/km

Sig/km

Sig/km

**3** Worksites are located on the

1	line	from	<input type="text"/> km	to	<input type="text"/> km	a maximum speed of	<input type="text"/> km/h
2	line	from	<input type="text"/> km	to	<input type="text"/> km	a maximum speed of	<input type="text"/> km/h
3	line	from	<input type="text"/> km	to	<input type="text"/> km	a maximum speed of	<input type="text"/> km/h
4	line	from	<input type="text"/> km	to	<input type="text"/> km	a maximum speed of	<input type="text"/> km/h
5	line	from	<input type="text"/> km	to	<input type="text"/> km	a maximum speed of	<input type="text"/> km/h
6	line	from	<input type="text"/> km	to	<input type="text"/> km	a maximum speed of	<input type="text"/> km/h
7	line	from	<input type="text"/> km	to	<input type="text"/> km	a maximum speed of	<input type="text"/> km/h
8	line	from	<input type="text"/> km	to	<input type="text"/> km	a maximum speed of	<input type="text"/> km/h

If speed restrictions are not applied above, rail traffic may travel at normal speed between worksites.

**4** A CLEARANCE sign is located at  km Normal speed may be resumed after passing this sign

**5** Issued to Driver/Track Vehicle Operator

name  rail traffic ID

**6** Issued by Signaller/Handsignaller

name  location/panel  hr  /  /

© Sydney Trains 2019

NRF 011 V 4.0

## Related Documents

NRF-011-Worksite-Warning.pdf

Form Procedures

# NPR 011 Using a Worksite Warning Form